

Author (also fact-checker)

Länsförsäkringar Bank Message Implementation Guidelines

For ISO 20022; CAMT053.001.02

Date	Version	Description	Author
2022-11-04	1.0	First version for publishing	
2025-11-14	1.1	Removal of P27 text	
2026-09-09	1.2	Clarifications, adding ERI information and textual updates	

Author (also fact-checker)

Contents

1	Introduction	4
1.1	Definitions	4
1.2	Character set	5
2	Message Specification CAMT.053	6
2.1	Document tag.....	6
2.2	Group Header	7
2.2.1	Message ID.....	7
2.2.2	Creation Date and Time	7
2.2.3	Message recipient	7
2.3	Statement.....	7
2.3.1	Identification	8
2.3.2	Creation date and Time	8
2.3.3	From To Date.....	8
2.3.4	Account.....	8
2.3.5	Balance	8
2.3.6	Transaction Summary.....	9
2.4	Entry.....	10
2.4.1	Entry Reference	10
2.4.2	Amount.....	10
2.4.3	Credit Debit Indicator	10
2.4.4	Status.....	10
2.4.5	Booking Date	10
2.4.6	Bank Transaction Code.....	11
2.4.7	Additional Entry Information	11
2.5	Entry Details	11
2.5.1	Batch.....	11
2.6	Transaction Details	12
2.6.1	References	12
2.6.2	Amount Details.....	12
2.6.2.1	Instructed amount.....	12

Author (also fact-checker)

2.6.2.2	Transaction amount	12
2.6.3	Related Parties	12
2.6.3.1	Debtor	13
2.6.3.2	Debtor Account	13
2.6.3.3	Ultimate Debtor	13
2.6.3.4	Creditor	13
2.6.3.5	Creditor Account	14
2.6.3.6	Ultimate Creditor	14
2.6.4	Related Agents	14
2.6.5	Local instrument	14
2.6.6	Purpose Code	14
2.6.7	Remittance Information	14
2.6.7.1	OCR numbers as structured reference	15
2.6.7.2	Extended remittance information (ERI)	15
2.6.8	Related Dates	15
3	XML structure	16
3.1	CAMT.053.001.02 Bank To Customer Statement	16
3.1.1	Overall Structure	16
3.1.2	Group Header	16
3.1.3	Statement	17
3.2	Common Structures	36
3.2.1	Cash Account 16	36
3.2.2	Party Identification	38
3.2.3	Postal Address	41
3.2.4	Branch And Financial Institution Identification	42
Appendix:		45
BTC codes		45
Changelog		49

1 Introduction

The Swedish banking market is adopting the international standard ISO20022 for payment messages. It will be a rollout over several years, and where we will develop new products and services around the credit transfer message for payments to bank accounts, Bankgiro numbers and Plusgiro numbers. It covers account transfers, bill payments, salary, pension, and social security benefits. Fully built, this new standard will improve integration with the international bank standards and benefit all our customers.

This document is a Message Implementation Guide for implementing usage of file reporting of account statements from Länsförsäkringar Bank. The account statement can be used to import all account transactions in a structured form to the customers system.

This version of the Message Implementation Guide describes the XML format CAMT.053.001.02 and how it is used by Länsförsäkringar Bank. Depending on type of transaction the amount of information will differ as Länsförsäkringar Bank has different information sets.

Incoming Bankgiro transactions which are booked on the account in one summarized transaction will be reported specifying all the included transactions.

1.1 Definitions

Term	Description
NPC	The Nordic Payments Council manage the Nordic payment schemes in the future to facilitate payments within the Nordic countries. The main objective for the NPC is to contribute to harmonised payments in the Nordics.
BIC	The Bank Identification Number is an international standard for bank identification.
IBAN	International Bank Account Number.
BBAN	The Basic Bank Account Number consists of a clearing number followed by the bank account number.
XML	Extensible Markup Language, an open standard messaging format.
XSD	An XML based schema to describe and validate an XML.

1.2 Character set


The ISO20022 XML message will follow UTF-8 character encoding. Characters used are the Latin character set commonly used in international communication and in addition to this the Scandinavian characters and the @-sign, as follows:

a b c d e f g h i j k l m n o p q r s t u v w x y z å ä ö æ ø
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z Å Ä Ö Æ Ø
0 1 2 3 4 5 6 7 8 9
/ - ? : () . , ' + @ Space

References, identifications, and identifiers must respect the following:

- Content is restricted to the Latin character set as defined above
- Content must not start or end with a '/'
- Content must not contain '/'s

2 Message Specification CAMT.053



In order to receive Account statements, the customer must subscribe to it. Once subscribed, they are sent to the customer in CAMT.053-format. The frequency can be chosen by the customer, but default frequency is once a day 7 days per week. An account statement will be produced regardless of if there are transaction to be reported or not. Opening balance and closing balance will be reported in the file based on calendar day period.

The statement will contain all monetary bookings on the account with detailed information (based on the information Länsförsäkringar Bank has received).


2.1 Document tag

Document tag is used to define the schema reference for the Camt.053 file. XML Schema or XSD is the xml document built to validate the attributes of an XML File. The XSD document will be shared for customers of the service to pre-validate the file in their own system before importing the file.

Example of a document tag: `<Document
xmlns:xsi=http://www.w3.org/2001/XMLSchema-instance
xmlns="urn:iso:std:iso:20022:tech:xsd:CAMT053_LF_CORP_O_V0">`

Author (also fact-checker)

2.2 Group Header



The group header holds information about the whole CAMT.053 message. It will include a unique message ID and creation date and time.

2.2.1 Message ID

The **MsgID** element is the identification of the message. It will be unique and will be structured as Date plus BIC (ELLFSESS) plus running number.


2.2.2 Creation Date and Time

The date and time format in element **CreDtTm** is from ISO8601.

2.2.3 Message recipient

This will not be used by Länsförsäkringar Bank at the moment.

2.3 Statement



Each statement is connected to one account only. In the ISO 20022 standard each message can include several statements. Länsförsäkringar Bank will send one message per account if a customer has subscribed to CAMT.053 account statements for several accounts. This can be changed in the future.

2.3.1 Identification

The statement identification number will be the MsgID plus a running number for the statement within the same message.

2.3.2 Creation date and Time

The date and time format in element **CreDtTm** is from ISO8601.

2.3.3 From To Date

Under this tag there will be both a start date and time and an end date and time for the account statement. All transactions booked on the account between these two times will be reported in the statement.

```
<FrToDt>
  <FrDtTm>2018-12-17T00:00:00+01:00</FrDtTm>
  <ToDtTm>2018-12-17T23:59:59+01:00</ToDtTm>
</FrToDt>
```

2.3.4 Account

Under this tag the reported account number will be sent in BBAN format. See example.

```
<Acct>
  <Id>
    <Othr>
      <Id>90201234567</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</Acct>
```

2.3.5 Balance

Länsförsäkringar Bank will report opening and closing balance for the period here.

Author (also fact-checker)

OPBD = Booked balance of the account at the beginning of the account reporting period. It always equals the closing booked balance from the previous report.

CLBD = Balance of the account at the end of the pre-agreed account reporting period. It is the sum of the opening booked balance at the beginning of the period and all entries booked to the account during the pre-agreed account reporting period.

```
<Bal>
  <Tp>
    <CdOrPrtry>
      <Cd>OPBD</Cd>
    </CdOrPrtry>
  </Tp>
  <Amt Ccy="SEK">1900</Amt>
  <CdtDbtInd>CRDT</CdtDbtInd>
  <Dt>
    <DtTm>2022-09-19T00:00:00</DtTm>
  </Dt>
</Bal>
<Bal>
  <Tp>
    <CdOrPrtry>
      <Cd>CLBD</Cd>
    </CdOrPrtry>
  </Tp>
  <Amt Ccy="SEK">1929</Amt>
  <CdtDbtInd>CRDT</CdtDbtInd>
  <Dt>
    <DtTm>2022-09-20T00:00:00</DtTm>
  </Dt>
</Bal>
```

2.3.6 Transaction Summary

Under this element Länsförsäkring Bank will report summary of credit entries and/or debit entries. It will be both number of entries and total sum for the included account entries.

Example:


```
<TxSummary>
  <TtlCdtNtries>
    <NbOfNtries>3</NbOfNtries>
    <Sum>44</Sum>
  </TtlCdtNtries>
```

Author (also fact-checker)

```

<TtlDbtNtries>
  <NbOfNtries>1</NbOfNtries>
  <Sum>15</Sum>
</TtlDbtNtries>
</TxSummary>
  
```

2.4 Entry



There will be one entry per transaction booked on the account. On this level information regarding the booked entry on the account will be presented. Some of the more detailed information will be handled in the transaction details.

2.4.1 Entry Reference

This is a unique ID for the entry set by Länsförsäkringar Bank.

2.4.2 Amount

In this tag the amount of the entry will be shown.

2.4.3 Credit Debit Indicator

This tag holds information if it is a debit (withdrawal from the account) or a credit (deposit on the account). The codes are DBIT and CRDT.

2.4.4 Status

The status of the entry reported will always be booked (BOOK).

2.4.5 Booking Date

This will be the date which the transaction was booked on the account.


2.4.6 Bank Transaction Code

Set of elements used to fully identify the type of underlying transaction resulting in an entry on account. Länsförsäkringar Bank will use the code structure as per ISO to define the type of transaction that has been booked on the account. See appendix for list of codes used by Länsförsäkringar Bank.

2.4.7 Additional Entry Information

In this field Länsförsäkringar Bank will report transaction texts (which also is viewable in the Internet Bank).

2.5 Entry Details




In this block there will be more details of the entry. For summarized bookings there will also be details on group level in the tag Batch.

2.5.1 Batch

In this block there will be information if the transaction is part of a batch booked entry. There are three different types of information in this tag. For salary transactions (via pain.001 or salary list) batch information will be reported but no details.

- MessageIdentification – will hold messageID from pain.001
- PaymentInformationIdentification – will hold ID from the payment information part in pain.001
- NumberOfTransactions – will be number of transaction details for this batch.

2.6 Transaction Details



For this block details regarding a transaction will be reported. For summarized booking on the account there can be many transaction details for one entry, for example for incoming Bankgiro transactions or batch booked transactions initiated via pain.001. For salary transactions the details regarding each transaction will not be reported, due to the sensitivity of the data. For reporting of details regarding salary transactions please see our camt.054 offering.

2.6.1 References

In this section there are several references included. Depending on type of transaction different references will be reported. For questions regarding a transaction to an officer in Länsförsäkringar Bank the best reference to use is the AccountServicerReference. This reference will be included also for salary transactions.

2.6.2 Amount Details

2.6.2.1 Instructed amount

Instructed amount will be reported for transactions in other currencies. It will be used for the amount in foreign currency.

2.6.2.2 Transaction amount

The transaction amount will always be included and will always be in the account currency (always SEK).

For transactions in other currencies currency exchange information will be reported under this tag.

2.6.3 Related Parties

Information regarding related parties if they exist and are allowed to be reported.

2.6.3.1 Debtor

This is the party that has been debited for the transaction. Will normally not be supplied for outgoing payments (debits on the account) as this is the account owner.

For debits this will be mapped for the following payment types:

- Card transactions – Merchant name if return
- File initiated payments – from pain.001 file
- Debtor name from Swish message
- Debtor name for incoming Bankgiro payments
- Debtor name for incoming NCT transactions

2.6.3.2 Debtor Account

This is the account that has been debited for the transaction.

For Swish payments the Swish number will be reported here both for outgoing and incoming transactions.

For outgoing payments done from own Bankgiro number, the BG number will be reported here.

For incoming payments from Bankgiro number or Plusgiro number these will be reported.

2.6.3.3 Ultimate Debtor

This will be reported if included in outgoing or incoming message.

2.6.3.4 Creditor

This is the party that has been credited for the transaction. For outgoing payments this will be the name supplied by the initiator if applicable. For incoming payments this will be the name coming from the debtor if applicable.

For Swish transactions this will be the name connected to the Swish number.

For outgoing Bankgiro and Plusgiro payments that Länsförsäkringar Bank will collect from the Bankgiro and Plusgiro catalogues.

2.6.3.5 **Creditor Account**

This is the account that has been credited for the transaction.

For Swish payments the Swish number NUMBER will be reported here both for outgoing and incoming transactions.

For incoming payments to own Bankgiro number, that Bankgiro number will be reported here.

For outgoing payments to Bankgiro number or Plusgiro number these will be reported.

2.6.3.6 **Ultimate Creditor**

This will be reported if included in outgoing or incoming message.

2.6.4 **Related Agents**

Only creditor agent used and only for outgoing Bankgiro and Plusgiro payments. For payments initiated via pain.001, the information in pain.001 will be reported here.

2.6.5 **Local instrument**

Local instrument sent with the transaction will be reported if applicable. For transactions following NPC rulebook there are two scenarios when this tag should be used, Extended remittance info (ERI) and Paper-initiated payment services.

For ERI the code will be PERI and it will be in the code field. For Paper-initiated payment services the code will be PAPR and sent in Proprietary field.

2.6.6 **Purpose Code**

Purpose code sent with the transaction will be reported here if it exists.

2.6.7 **Remittance Information**

Under this tag Länsförsäkringar Bank will report the remittance information we have received from the initiator. It can be supplied as Unstructured or Structured remittance information. For incoming messages not following ISO 20022 or the same version of ISO 20022 Länsförsäkringar Bank will map the information to this version of ISO 20022 fields.

There are two fields in structured remittance information that can hold ID:s. These two fields are used differently depending on sender and which information that is supplied on the invoice. For invoice numbers the field Structured/Referred Document Information/Number is used and for OCR numbers the field Structured/Creditor Reference Information/Reference should be used (see below).

2.6.7.1 OCR numbers as structured reference

For incoming transactions with OCR numbers as reference these will be reported in the structured remittance info. See example:

```

<RmtInf>
  <Strd>
    <CdtrRefInf>
      <Tp>
        <CdOrPrtry>
          <Cd>SCOR</Cd>
        </CdOrPrtry>
      </Tp>
      <Ref>85858</Ref>
    </CdtrRefInf>
  </Strd>
</RmtInf>

```

2.6.7.2 Extended remittance information (ERI)

For remittance information with several structured remittance information Länsförsäkringar Bank will forward the information we receive in incoming messages. In most cases the structured remittance information will include amounts for each structured remittance info and the sender/sending bank should verify that the amounts summarize to the transaction amount.

Note that the amount field “Credit Note Amount” (CdtNoteAmt) should be considered as negative amount when doing the summarization.

2.6.8 Related Dates

Under this tag Länsförsäkringar Bank will report the transaction date for a card transaction. The field name for this is TxDtTm.

3 XML structure

3.1 CAMT.053.001.02 Bank To Customer Statement

The XML structure matrix is divided into groups, so it should be easy to find different parts. Only the sections handled by LF in any way will show up here.

Some elements represent an exclusive choice between two or more child elements. These child elements are marked with XOR to indicate they belong to an XOR-split, where the choice of one element is mandatory. The multiplicity of an element is notated with an interval notation, like x..y, meaning x is the minimum number of occurrences of an element, and y is the maximum.

3.1.1 Overall Structure

Mult	Message Element	Customer to Bank Credit Transfer Information	
	Document	XML Tag Type	Document Document
1..1	Bank To Customer Statement V02	ISO Name ISO Definition	Bank To Customer Statement V02 The BankToCustomerStatement message is sent by the account servicer to an account owner or to a party authorised by the account owner to receive the message. It is used to inform the account owner, or authorised party, of the entries booked to the account, and to provide the owner with balance information on the account at a given point in time.
		XML Tag Type	BkToCstmrStmt BankToCustomerStatementV02
1..1	Bank To Customer Statement V02 +Group Header	ISO Name ISO Definition XML Tag Type More Details	Group Header Common information for the message. GrpHdr GroupHeader42 See Group Header .
1..n	Bank To Customer Statement V02 +Statement	ISO Name ISO Definition XML Tag Type More Details	Statement Reports on booked entries and balances for a cash account. Stmt AccountStatement2 See Account Statement .

3.1.2 Group Header

Mult	Message Element	Customer to Bank Credit Transfer Information
------	-----------------	--

Author (also fact-checker)

1..1	GroupHeader42 +Message Identification	ISO Name ISO Definition XML Tag Type	Message Identification Point to point reference, as assigned by the account servicing institution, and sent to the account owner or the party authorised to receive the message, to unambiguously identify the message. Usage: The account servicing institution has to make sure that MessageIdentification is unique per account owner for a pre-agreed period. MsgId Max35Text
1..1	GroupHeader42 +Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODatetime
0..1	GroupHeader42 +Message Recipient	ISO Name ISO Definition XML Tag Type More Details	Message Recipient Party authorised by the account owner to receive information about movements on the account. Usage: MessageRecipient should only be identified when different from the account owner. MsgRcpt PartyIdentification32 See Party Identification .
0..1	GroupHeader42 +Additional Information	ISO Name ISO Definition XML Tag Type	Additional Information Further details of the message. AddtInf Max500Text

3.1.3 Statement

Mult	Message Element	Customer to Bank Credit Transfer Information	
1..1	AccountStatement2 +Identification	ISO Name ISO Definition XML Tag Type	Identification Unique identification, as assigned by the account servicer, to unambiguously identify the account statement. Id Max35Text
1..1	AccountStatement2 +Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODatetime

Author (also fact-checker)

0..1	AccountStatement2 +From To Date	ISO Name ISO Definition XML Tag Type	From To Date Range of time between a start date and an end date for which the account statement is issued. FrToDt DateTimePeriodDetails
1..1	AccountStatement2 +From To Date ++From Date Time	ISO Name ISO Definition XML Tag Type	From Date Time Date and time at which the range starts. FrDtTm ISODateTime
1..1	AccountStatement2 +From To Date ++To Date Time	ISO Name ISO Definition XML Tag Type	To Date Time Date and time at which the range ends. ToDtTm ISODateTime
1..1	AccountStatement2 +Account	ISO Name ISO Definition XML Tag Type	Account Unambiguous identification of the account to which credit and debit entries are made. Acct CashAccount20
1..1	AccountStatement2 +Account ++Identification	ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification for the account between the account owner and the account servicer. Id AccountIdentification4Choice
XOR 1..1	AccountStatement2 +Account ++Identification +++IBAN	ISO Name ISO Definition XML Tag Type	IBAN International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions. IBAN IBAN2007Identifier
XOR 1..1	AccountStatement2 +Account ++Identification +++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an account, as assigned by the account servicer, using an identification scheme. Othr GenericAccountIdentification1
1..1	AccountStatement2 +Account ++Identification +++Other ++++Identification	ISO Name ISO Definition XML Tag Type	Identification Identification assigned by an institution. Id Max34Text

Author (also fact-checker)

0..1	AccountStatement2 +Account ++Identification +++Other ++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm AccountSchemeName1Choice
XOR 1..1	AccountStatement2 +Account ++Identification +++Other ++++Scheme Name +++++Code	ISO Name ISO Definition XML Tag Type	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalAccountIdentification1Code
XOR 1..1	AccountStatement2 +Account ++Identification +++Other ++++Scheme Name +++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text
0..1	AccountStatement2 +Account ++Identification +++Other ++++Issuer	ISO Name ISO Definition XML Tag Type	Issuer Entity that assigns the identification. Issr Max35Text
0..1	AccountStatement2 +Account ++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the nature, or use of the account. Tp CashAccountType2
1..1	AccountStatement2 +Account ++Type +++Code	ISO Name ISO Definition XML Tag Type	Code Account type, in a coded form. Cd CashAccountType4Code
1..1	AccountStatement2 +Account ++Type +++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Nature or use of the account in a proprietary form. Prtry Max35Text
0..1	AccountStatement2 +Account ++Currency	ISO Name ISO Definition XML Tag Type	Currency Identification of the currency in which the account is held. Ccy ActiveOrHistoricCurrencyCode

Author (also fact-checker)

0..1	AccountStatement2 +Account ++Name	ISO Name ISO Definition XML Tag Type	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account. Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text
0..1	AccountStatement2 +Account ++Owner	ISO Name ISO Definition XML Tag Type More Details	Owner Party that legally owns the account. Ownr PartyIdentification32 See Party Identification .
0..1	AccountStatement2 +Account ++Servicer	ISO Name ISO Definition XML Tag Type More Details	Servicer Party that manages the account on behalf of the account owner, that is manages the registration and booking of entries on the account, calculates balances on the account and provides information about the account. Svcr BranchAndFinancialInstitutionIdentification4 See Branch And Financial Institution Identification .
0..1	AccountStatement2 +Related Account	ISO Name ISO Definition XML Tag Type More Details LF Usage	Related Account Identifies the parent account of the account for which the statement has been issued. RltdAcct CashAccount16 See Cash Account 16 Not used by Länsförsäkringar Bank
1..n	AccountStatement2 +Balance	ISO Name ISO Definition XML Tag Type	Balance Set of elements used to define the balance as a numerical representation of the net increases and decreases in an account at a specific point in time. Bal CashBalance3
1..1	AccountStatement2 +Balance ++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the nature of a balance. Tp BalanceType12
1..1	AccountStatement2 +Balance ++Type +++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Coded or proprietary format balance type. CdOrPrtry BalanceType5Choice

Author (also fact-checker)

XOR 1..1	AccountStatement2 +Balance ++Type +++Code Or Proprietary ++++Code	ISO Name ISO Definition XML Tag Type	Code Balance type, in a coded form. Cd BalanceType12Code
XOR 1..1	AccountStatement2 +Balance ++Type +++Code Or Proprietary ++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Balance type, in a proprietary form. Prtry Max35Text
1..1	AccountStatement2 +Balance ++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money of the cash balance. Amt ActiveOrHistoricCurrencyAndAmount
1..1	AccountStatement2 +Balance ++Credit Debit Indicator	ISO Name ISO Definition XML Tag Type	Credit Debit Indicator Indicates whether the balance is a credit or a debit balance. Usage: A zero balance is considered to be a credit balance. CdtDbtInd CreditDebitCode
1..1	AccountStatement2 +Balance ++Date	ISO Name ISO Definition XML Tag Type	Date Indicates the date (and time) of the balance. Dt DateAndDateTimeChoice
XOR 1..1	AccountStatement2 +Balance ++Date +++Date	ISO Name ISO Definition XML Tag Type	Date Specified date. Dt ISODate
0..1	AccountStatement2 +Transactions Summary	ISO Name ISO Definition XML Tag Type	Transactions Summary Set of elements used to provide summary information on entries. Txssummry TotalTransactions2
0..1	AccountStatement2 +Transactions Summary ++Total Credit Entries	ISO Name ISO Definition XML Tag Type	Total Credit Entries Specifies the total numb6,3er and sum of credit entries. TtlCdtNtries NumberAndSumOfTransactions1
0..1	AccountStatement2 +Transactions Summary ++Total Credit Entries +++Number Of Entries	ISO Name ISO Definition XML Tag Type	Number Of Entries Number of individual entries included in the report. NbOfNtries Max15NumericText
0..1	AccountStatement2 +Transactions Summary ++Total Credit Entries +++Sum	ISO Name ISO Definition XML Tag Type	Sum Total of all individual entries included in the report. Sum DecimalNumber

Author (also fact-checker)

0..1	AccountStatement2 +Transactions Summary ++Total Debit Entries	ISO Name ISO Definition XML Tag Type	Total Debit Entries Specifies the total number and sum of debit entries. TtlDbtNtries NumberAndSumOfTransactions1
0..1	AccountStatement2 +Transactions Summary ++Total Debit Entries +++Number Of Entries	ISO Name ISO Definition XML Tag Type	Number Of Entries Number of individual entries included in the report. NbOfNtries Max15NumericText
0..1	AccountStatement2 +Transactions Summary ++Total Debit Entries +++Sum	ISO Name ISO Definition XML Tag Type	Sum Total of all individual entries included in the report. Sum DecimalNumber
0..n	AccountStatement2 +Entry	ISO Name ISO Definition XML Tag Type	Entry Set of elements used to specify an entry in the statement. Usage: At least one reference must be provided to identify the entry and its underlying transaction(s). Ntry ReportEntry2
0..1	AccountStatement2 +Entry ++Entry Reference	ISO Name ISO Definition XML Tag Type	Entry Reference Unique reference for the entry. NtryRef Max35Text
1..1	AccountStatement2 +Entry ++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money in the cash entry. Amt ActiveOrHistoricCurrencyAndAmount
1..1	AccountStatement2 +Entry ++Credit Debit Indicator	ISO Name ISO Definition XML Tag Type	Credit Debit Indicator Indicates whether the entry is a credit or a debit entry. CdtDbtInd CreditDebitCode
1..1	AccountStatement2 +Entry ++Status	ISO Name ISO Definition XML Tag Type	Status Status of an entry on the books of the account servicer. Sts EntryStatus2Code
0..1	AccountStatement2 +Entry ++Booking Date	ISO Name ISO Definition XML Tag Type	Booking Date Date and time when an entry is posted to an account on the account servicer's books. Usage: Booking date is the expected booking date, unless the status is booked, in which case it is the actual booking date. BookgDt DateAndDateTimeChoice
XOR 1..1	AccountStatement2 +Entry ++Booking Date +++Date	ISO Name ISO Definition XML Tag Type	Date Specified date. Dt ISODate

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Value Date	ISO Name ISO Definition XML Tag Type LF Usage	Value Date Date and time at which assets become available to the account owner in case of a credit entry, or cease to be available to the account owner in case of a debit entry. Usage: If entry status is pending and value date is present, then the value date refers to an expected/requested value date. For entries subject to availability/float and for which availability information is provided, the value date must not be used. In this case the availability component identifies the number of availability days. ValDt DateAndDateTimeChoice Not used by Länsförsäkringar Bank
XOR 1..1	AccountStatement2 +Entry ++Value Date +++Date	ISO Name ISO Definition XML Tag Type	Date Specified date. Dt ISODate
0..1	AccountStatement2 +Entry ++Account Servicer Reference	ISO Name ISO Definition XML Tag Type LF Usage	Account Servicer Reference Unique reference as assigned by the account servicing institution to unambiguously identify the entry. AcctSvcrRef Max35Text Not used by Länsförsäkringar Bank
1..1	AccountStatement2 +Entry ++Bank Transaction Code	ISO Name ISO Definition XML Tag Type	Bank Transaction Code Set of elements used to fully identify the type of underlying transaction resulting in an entry. BkTxCd BankTransactionCodeStructure4
0..1	AccountStatement2 +Entry ++Bank Transaction Code +++Domain	ISO Name ISO Definition XML Tag Type	Domain Set of elements used to provide the domain, the family and the sub-family of the bank transaction code, in a structured and hierarchical format. Usage: If a specific family or sub-family code cannot be provided, the generic family code defined for the domain or the generic sub-family code defined for the family should be provided. Domn BankTransactionCodeStructure5
1..1	AccountStatement2 +Entry ++Bank Transaction Code +++Domain ++++Code	ISO Name ISO Definition XML Tag Type	Code Specifies the business area of the underlying transaction. Cd ExternalBankTransactionDomain1Code

Author (also fact-checker)

1..1	AccountStatement2 +Entry ++Bank Transaction Code +++Domain ++++Family	ISO Name ISO Definition XML Tag Type	Family Specifies the family and the sub-family of the bank transaction code, within a specific domain, in a structured and hierarchical format. Fmly BankTransactionCodeStructure6
1..1	AccountStatement2 +Entry ++Bank Transaction Code +++Domain ++++Family +++++Code	ISO Name ISO Definition XML Tag Type	Code Specifies the family within a domain. Cd ExternalBankTransactionFamily1Code
1..1	AccountStatement2 +Entry ++Bank Transaction Code +++Domain ++++Family +++++Sub Family Code	ISO Name ISO Definition XML Tag Type	Sub Family Code Specifies the sub-product family within a specific family. SubFmlyCd ExternalBankTransactionSubFamily1Code
0..n	AccountStatement2 +Entry ++Entry Details	ISO Name ISO Definition XML Tag Type	Entry Details Set of elements used to provide details on the entry. NtryDtls EntryDetails1
0..1	AccountStatement2 +Entry ++Entry Details +++Batch	ISO Name ISO Definition XML Tag Type	Batch Set of elements used to provide details on batched transactions. Btch BatchInformation2
0..1	AccountStatement2 +Entry ++Entry Details +++Batch ++++Message Identification	ISO Name ISO Definition XML Tag Type	Message Identification Point to point reference, as assigned by the sending party, to unambiguously identify the batch of transactions. MsgId Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Batch ++++Payment Information Identification	ISO Name ISO Definition XML Tag Type	Payment Information Identification Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message. PmtInfid Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Batch ++++Number Of Transactions	ISO Name ISO Definition XML Tag Type	Number Of Transactions Number of individual transactions included in the batch. NbOfTxs Max15NumericText
0..n	AccountStatement2 +Entry ++Entry Details +++Transaction Details	ISO Name ISO Definition XML Tag Type	Transaction Details Set of elements used to provide information on the underlying transaction(s). TxDtls EntryTransaction2

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References	ISO Name ISO Definition XML Tag Type	References Set of elements used to provide the identification of the underlying transaction. Refs TransactionReferences2
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References +++++Message Identification	ISO Name ISO Definition XML Tag Type	Message Identification Point to point reference, as assigned by the instructing party of the underlying message. MsgId Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References +++++Account Servicer Reference	ISO Name ISO Definition XML Tag Type	Account Servicer Reference Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction. AcctSvcrRef Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References +++++Payment Information Identification	ISO Name ISO Definition XML Tag Type	Payment Information Identification Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message. PmtInflid Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References +++++Instruction Identification	ISO Name ISO Definition XML Tag Type	Instruction Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction. Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction. InstrId Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References +++++End To End Identification	ISO Name ISO Definition XML Tag Type	End To End Identification Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain. Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction. Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain. EndToEndId Max35Text

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References +++++Transaction Identification	ISO Name ISO Definition XML Tag Type	Transaction Identification Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain. Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level. Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period. TxId Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References +++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Proprietary reference related to the underlying transaction. Prtry ProprietaryReference1
1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References +++++Proprietary +++++Type	ISO Name ISO Definition XML Tag Type	Type Identifies the type of reference reported. Tp Max35Text
1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++References +++++Proprietary +++++Reference	ISO Name ISO Definition XML Tag Type	Reference Proprietary reference specification related to the underlying transaction. Ref Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details	ISO Name ISO Definition XML Tag Type	Amount Details Set of elements providing detailed information on the original amount. Usage: This component (on transaction level) should be used in case booking is for a single transaction and the original amount is different from the entry amount. It can also be used in case individual original amounts are provided in case of a batch or aggregate booking. AmtDtls AmountAndCurrencyExchange3

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details +++++Instructed Amount	ISO Name ISO Definition XML Tag Type	Instructed Amount Identifies the amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party and provides currency exchange information in case the instructed amount and/or currency is/are different from the entry amount and/or currency. InstdAmt AmountAndCurrencyExchangeDetails3
1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details +++++Instructed Amount ++++++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt ActiveOrHistoricCurrencyAndAmount
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details +++++Transaction Amount	ISO Name ISO Definition XML Tag Type	Transaction Amount Amount of the underlying transaction. TxAmt AmountAndCurrencyExchangeDetails3
1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details +++++Transaction Amount ++++++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt ActiveOrHistoricCurrencyAndAmount
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details +++++Transaction Amount ++++++Currency Exchange	ISO Name ISO Definition XML Tag Type	Currency Exchange Set of elements used to provide details on the currency exchange. CcyXchg CurrencyExchange5
1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details +++++Transaction Amount ++++++Currency Exchange +++++++Source Currency	ISO Name ISO Definition XML Tag Type	Source Currency Currency from which an amount is to be converted in a currency conversion. SrcCcy ActiveOrHistoricCurrencyCode

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details +++++Transaction Amount +++++Currency Exchange +++++Target Currency	ISO Name ISO Definition XML Tag Type	Target Currency Currency into which an amount is to be converted in a currency conversion. TrgtCcy ActiveOrHistoricCurrencyCode
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details +++++Transaction Amount +++++Currency Exchange +++++Unit Currency	ISO Name ISO Definition XML Tag Type	Unit Currency Currency in which the rate of exchange is expressed in a currency exchange. In the example 1GBP = xxxCUR, the unit currency is GBP. UnitCcy ActiveOrHistoricCurrencyCode
1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Amount Details +++++Transaction Amount +++++Currency Exchange +++++Exchange Rate	ISO Name ISO Definition XML Tag Type	Exchange Rate Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency. Usage: ExchangeRate expresses the ratio between UnitCurrency and QuotedCurrency (ExchangeRate = UnitCurrency/QuotedCurrency). XchgRate BaseOneRate
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Parties	ISO Name ISO Definition XML Tag Type	Related Parties Set of elements used to identify the parties related to the underlying transaction. RltdPties TransactionParty2
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Parties ++++Debtor	ISO Name ISO Definition XML Tag Type More Details	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification32 See Party Identification .
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Parties ++++Debtor Account	ISO Name ISO Definition XML Tag Type More Details	Debtor Account Unambiguous identification of the account of the debtor. DbtrAcct CashAccount16 See Cash Account 16 .
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Parties ++++Ultimate Debtor	ISO Name ISO Definition XML Tag Type More Details	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr PartyIdentification32 See Party Identification .

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Parties +++++Creditor	ISO Name ISO Definition XML Tag Type More Details	Creditor Party to which an amount of money is due. Cdtr PartyIdentification32 See Party Identification .
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Parties +++++Creditor Account	ISO Name ISO Definition XML Tag Type More Details	Creditor Account Unambiguous identification of the account of the creditor to which a credit entry has been posted as a result of the payment transaction. CdtrAcct CashAccount16 See Cash Account 16 .
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Parties +++++Ultimate Creditor	ISO Name ISO Definition XML Tag Type More Details	Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr PartyIdentification32 See Party Identification .
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Agents	ISO Name ISO Definition XML Tag Type	Related Agents Set of elements used to identify the agents related to the underlying transaction. RltdAgts TransactionAgents2
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Agents +++++Debtor Agent	ISO Name ISO Definition XML Tag Type More Details	Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification4 See Branch And Financial Institution Identification .
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Agents +++++Creditor Agent	ISO Name ISO Definition XML Tag Type More Details	Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification4 See Branch And Financial Institution Identification .
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Purpose	ISO Name ISO Definition XML Tag Type	Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice

Author (also fact-checker)

XOR 1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Purpose ++++Code	ISO Name ISO Definition XML Tag Type	Code Underlying reason for the payment transaction, as published in an external purpose code list. Cd ExternalPurpose1Code
XOR 1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Purpose ++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Purpose, in a proprietary form. Prtry Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information	ISO Name ISO Definition XML Tag Type	Remittance Information Structured information that enables the matching, ie, reconciliation, of a payment with the items that the payment is intended to settle, such as commercial invoices in an account receivable system. RmtInf RemittanceInformation5
0..n	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information ++++Unstructured	ISO Name ISO Definition XML Tag Type	Unstructured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form. Ustrd Max140Text
0..999	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information ++++Structured	ISO Name ISO Definition XML Tag Type	Structured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form. Strd StructuredRemittanceInformation7
0..n	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information ++++Structured +++++Referred Document Information	ISO Name ISO Definition XML Tag Type	Referred Document Information Set of elements used to identify the documents referred to in the remittance information. RfrdDocInf ReferredDocumentInformation3
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information ++++Structured +++++Referred Document Information +++++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the type of referred document. Tp ReferredDocumentType2

Author (also fact-checker)

1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Information ++++++Type +++++++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Provides the type details of the referred document. CdOrPrtry ReferredDocumentType1Choice
XOR 1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Information ++++++Type +++++++Code Or Proprietary +++++++Code	ISO Name ISO Definition XML Tag Type	Code Document type in a coded form. Cd DocumentType5Code
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Information ++++++Type +++++++Issuer	ISO Name ISO Definition XML Tag Type	Issuer Identification of the issuer of the reference document type. Issr Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Information +++++++Number	ISO Name ISO Definition XML Tag Type	Number Unique and unambiguous identification of the referred document. Nb Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Information +++++++Related Date	ISO Name ISO Definition XML Tag Type	Related Date Date associated with the referred document. RltdDt ISODate
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount	ISO Name ISO Definition XML Tag Type	Referred Document Amount Set of elements used to provide details on the amounts of the referred document. RfrdDocAmt RemittanceAmount1

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount ++++++Due Payable Amount	ISO Name ISO Definition XML Tag Type	Due Payable Amount Amount specified is the exact amount due and payable to the creditor. DuePyblAmt ActiveOrHistoricCurrencyAndAmount
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount ++++++Discount Applied Amount	ISO Name ISO Definition XML Tag Type	Discount Applied Amount Amount of money that results from the application of an agreed discount to the amount due and payable to the creditor. DscntApldAmt ActiveOrHistoricCurrencyAndAmount
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount ++++++Credit Note Amount	ISO Name ISO Definition XML Tag Type	Credit Note Amount Amount specified for the referred document is the amount of a credit note. CdtNoteAmt ActiveOrHistoricCurrencyAndAmount
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount ++++++Tax Amount	ISO Name ISO Definition XML Tag Type	Tax Amount Quantity of cash resulting from the calculation of the tax. TaxAmt ActiveOrHistoricCurrencyAndAmount
0..n	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount ++++++Adjustment Amount And Reason	ISO Name ISO Definition XML Tag Type	Adjustment Amount And Reason Set of elements used to provide information on the amount and reason of the document adjustment. AdjstmntAmtAndRsn DocumentAdjustment1
1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount ++++++Adjustment Amount And Reason ++++++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money of the document adjustment. Amt ActiveOrHistoricCurrencyAndAmount

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount ++++++Adjustment Amount And Reason +++++++Credit Debit Indicator	ISO Name ISO Definition XML Tag Type	Credit Debit Indicator Specifies whether the adjustment must be subtracted or added to the total amount. CdtDbtInd CreditDebitCode
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount ++++++Adjustment Amount And Reason +++++++Reason	ISO Name ISO Definition XML Tag Type	Reason Specifies the reason for the adjustment. Rsn Max4Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount ++++++Adjustment Amount And Reason +++++++Additional Information	ISO Name ISO Definition XML Tag Type	Additional Information Provides further details on the document adjustment. AddtlInf Max140Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Referred Document Amount +++++++Remitted Amount	ISO Name ISO Definition XML Tag Type	Remitted Amount Amount of money remitted for the referred document. RmtdAmt ActiveOrHistoricCurrencyAndAmount
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Creditor Reference Information	ISO Name ISO Definition XML Tag Type	Creditor Reference Information Reference information provided by the creditor to allow the identification of the underlying documents. CdtrRefInf CreditorReferenceInformation2
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Creditor Reference Information +++++++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the type of creditor reference. Tp CreditorReferenceType2

Author (also fact-checker)

1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Creditor Reference Information +++++++Type +++++++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Coded or proprietary format creditor reference type. CdOrPrtry CreditorReferenceType1Choice
XOR 1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Creditor Reference Information +++++++Type +++++++Code Or Proprietary +++++++Code	ISO Name ISO Definition XML Tag Type	Code Type of creditor reference, in a coded form. Cd DocumentType3Code
XOR 1..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Creditor Reference Information +++++++Type +++++++Code Or Proprietary +++++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Creditor reference type, in a proprietary form. Prtry Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Creditor Reference Information +++++++Type +++++++Issuer	ISO Name ISO Definition XML Tag Type	Issuer Entity that assigns the credit reference type. Issr Max35Text

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Creditor Reference Information ++++++Reference	ISO Name ISO Definition XML Tag Type	Reference Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction. Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money. If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification. Ref Max35Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Invoicer	ISO Name ISO Definition XML Tag Type More Details	Invoicer Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor. Invcr PartyIdentification32 See Party Identification .
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Invoicee	ISO Name ISO Definition XML Tag Type More Details	Invoicee Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor. Invcee PartyIdentification32 See Party Identification .
0..3	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Remittance Information +++++Structured ++++++Additional Remittance Information	ISO Name ISO Definition XML Tag Type	Additional Remittance Information Additional information, in free text form, to complement the structured remittance information. AddtlRmtInf Max140Text
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Dates	ISO Name ISO Definition XML Tag Type	Related Dates Set of elements used to identify the dates related to the underlying transactions. RltdDts TransactionDates2
0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Related Dates +++++Transaction Date Time	ISO Name ISO Definition XML Tag Type	Transaction Date Time Date and time of the underlying transaction. TxDtTm ISODatetime

Author (also fact-checker)

0..1	AccountStatement2 +Entry ++Entry Details +++Transaction Details ++++Additional Transaction Information	ISO Name ISO Definition XML Tag Type	Additional Transaction Information Further details of the transaction. AddtlTxInf Max500Text
0..1	AccountStatement2 +Entry ++Additional Entry Information	ISO Name ISO Definition XML Tag Type	Additional Entry Information Further details of the entry. AddtlNtryInf Max500Text
0..1	AccountStatement2 +Additional Statement Information	ISO Name ISO Definition XML Tag Type	Additional Statement Information Further details of the account statement. AddtlStmntInf Max500Text

3.2 Common Structures

3.2.1 Cash Account 16

Mult	Message Element	Customer to Bank Credit Transfer Information	
1..1	CashAccount16 +Identification	ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification for the account between the account owner and the account servicer. Id AccountIdentification4Choice
XOR 1..1	CashAccount16 +Identification ++IBAN	ISO Name ISO Definition XML Tag Type	IBAN International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions. IBAN IBAN2007Identifier
XOR 1..1	CashAccount16 +Identification ++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an account, as assigned by the account servicer, using an identification scheme. Othr GenericAccountIdentification1
1..1	CashAccount16 +Identification ++Other +++Identification	ISO Name ISO Definition XML Tag Type	Identification Identification assigned by an institution. Id Max34Text

Author (also fact-checker)

0..1	CashAccount16 +Identification ++Other +++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm AccountSchemeName1Choice
XOR 1..1	CashAccount16 +Identification ++Other +++Scheme Name ++++Code	ISO Name ISO Definition XML Tag Type	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalAccountIdentification1Code
XOR 1..1	CashAccount16 +Identification ++Other +++Scheme Name ++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text
0..1	CashAccount16 +Identification ++Other +++Issuer	ISO Name ISO Definition XML Tag Type	Issuer Entity that assigns the identification. Issr Max35Text
0..1	CashAccount16 +Type	ISO Name ISO Definition XML Tag Type	Type Specifies the nature, or use of the account. Tp CashAccountType2
1..1	CashAccount16 +Type ++Code	ISO Name ISO Definition XML Tag Type	Code Account type, in a coded form. Cd CashAccountType4Code
1..1	CashAccount16 +Type ++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Nature or use of the account in a proprietary form. Prtry Max35Text
0..1	CashAccount16 +Currency	ISO Name ISO Definition XML Tag Type	Currency Identification of the currency in which the account is held. Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account. Ccy ActiveOrHistoricCurrencyCode

Author (also fact-checker)

0..1	CashAccount16 +Name	ISO Name Name ISO Definition Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account. Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. XML Tag Nm Type Max70Text
------	------------------------	--

3.2.2 Party Identification

Mult	Message Element	Customer to Bank Credit Transfer Information	
0..1	PartyIdentification32 +Name	ISO Name Name ISO Definition Name by which a party is known and which is usually used to identify that party. XML Tag Nm Type Max140Text	
0..1	PartyIdentification32 +Postal Address	ISO Name Postal Address ISO Definition Information that locates and identifies a specific address, as defined by postal services. XML Tag PstlAdr Type PostalAddress6 More Details See Postal Address .	
0..1	PartyIdentification32 +Identification	ISO Name Identification ISO Definition Unique and unambiguous identification of a party. XML Tag Id Type Party6Choice	
XOR 1..1	PartyIdentification32 +Identification ++Organisation Identification	ISO Name Organisation Identification ISO Definition Unique and unambiguous way to identify an organisation. XML Tag OrgId Type OrganisationIdentification4	
0..1	PartyIdentification32 +Identification ++Organisation Identification +++BICOrBEI	ISO Name BICOrBEI ISO Definition Code allocated to a financial institution or non financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". XML Tag BICOrBEI Type AnyBICIdentifier	

Author (also fact-checker)

0..n	PartyIdentification32 +Identification ++Organisation Identification +++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an organisation, as assigned by an institution, using an identification scheme. Othr GenericOrganisationIdentification1
1..1	PartyIdentification32 +Identification ++Organisation Identification +++Other ++++Identification	ISO Name ISO Definition XML Tag Type	Identification Identification assigned by an institution. Id Max35Text
0..1	PartyIdentification32 +Identification ++Organisation Identification +++Other ++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm OrganisationIdentificationSchemeName1Choice
XOR 1..1	PartyIdentification32 +Identification ++Organisation Identification +++Other ++++Scheme Name +++++Code	ISO Name ISO Definition XML Tag Type	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalOrganisationIdentification1Code
XOR 1..1	PartyIdentification32 +Identification ++Organisation Identification +++Other ++++Scheme Name +++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text
0..1	PartyIdentification32 +Identification ++Organisation Identification +++Other ++++Issuer	ISO Name ISO Definition XML Tag Type	Issuer Entity that assigns the identification. Issr Max35Text
XOR 1..1	PartyIdentification32 +Identification ++Private Identification	ISO Name ISO Definition XML Tag Type	Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification5
0..1	PartyIdentification32 +Identification ++Private Identification +++Date And Place Of Birth	ISO Name ISO Definition XML Tag Type	Date And Place Of Birth Date and place of birth of a person. DtAndPlcOfBirth DateAndPlaceOfBirth
1..1	PartyIdentification32 +Identification ++Private Identification +++Date And Place Of Birth ++++Birth Date	ISO Name ISO Definition XML Tag Type	Birth Date Date on which a person is born. BirthDt ISODate

Author (also fact-checker)

0..1	PartyIdentification32 +Identification ++Private Identification +++Date And Place Of Birth ++++Province Of Birth	ISO Name ISO Definition XML Tag Type	Province Of Birth Province where a person was born. PrvcOfBirth Max35Text
1..1	PartyIdentification32 +Identification ++Private Identification +++Date And Place Of Birth ++++City Of Birth	ISO Name ISO Definition XML Tag Type	City Of Birth City where a person was born. CityOfBirth Max35Text
1..1	PartyIdentification32 +Identification ++Private Identification +++Date And Place Of Birth ++++Country Of Birth	ISO Name ISO Definition XML Tag Type	Country Of Birth Country where a person was born. CtryOfBirth CountryCode
0..n	PartyIdentification32 +Identification ++Private Identification +++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of a person, as assigned by an institution, using an identification scheme. Othr GenericPersonIdentification1
1..1	PartyIdentification32 +Identification ++Private Identification +++Other ++++Identification	ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification of a person. Id Max35Text
0..1	PartyIdentification32 +Identification ++Private Identification +++Other ++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm PersonIdentificationSchemeName1Choice
XOR 1..1	PartyIdentification32 +Identification ++Private Identification +++Other ++++Scheme Name +++++Code	ISO Name ISO Definition XML Tag Type	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalPersonIdentification1Code
XOR 1..1	PartyIdentification32 +Identification ++Private Identification +++Other ++++Scheme Name +++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text
0..1	PartyIdentification32 +Identification ++Private Identification +++Other ++++Issuer	ISO Name ISO Definition XML Tag Type	Issuer Entity that assigns the identification. Issr Max35Text

Author (also fact-checker)

0..1	PartyIdentification32 +Country Of Residence	ISO Name ISO Definition XML Tag Type	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode
------	--	---	--

3.2.3 Postal Address

Mult	Message Element	Customer to Bank Credit Transfer Information	
0..1	PostalAddress6 +Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType2Code
0..1	PostalAddress6 +Department	ISO Name ISO Definition XML Tag Type	Department Identification of a division of a large organisation or building. Dept Max70Text
0..1	PostalAddress6 +Sub Department	ISO Name ISO Definition XML Tag Type	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text
0..1	PostalAddress6 +Street Name	ISO Name ISO Definition XML Tag Type	Street Name Name of a street or thoroughfare. StrtNm Max70Text
0..1	PostalAddress6 +Building Number	ISO Name ISO Definition XML Tag Type	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text
0..1	PostalAddress6 +Post Code	ISO Name ISO Definition XML Tag Type	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text
0..1	PostalAddress6 +Town Name	ISO Name ISO Definition XML Tag Type	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text
0..1	PostalAddress6 +Country Sub Division	ISO Name ISO Definition XML Tag Type	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text

Author (also fact-checker)

0..1	PostalAddress6 +Country	ISO Name ISO Definition XML Tag Type	Country Nation with its own government. Ctry CountryCode
0..7	PostalAddress6 +Address Line	ISO Name ISO Definition XML Tag Type	Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text

3.2.4 Branch And Financial Institution Identification

Mult	Message Element	Customer to Bank Credit Transfer Information	
1..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification	ISO Name ISO Definition XML Tag Type	Financial Institution Identification Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. FinInstnId FinancialInstitutionIdentification7
0..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++BIC	ISO Name ISO Definition XML Tag Type	BIC Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". BIC BICIdentifier
0..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Clearing System Member Identification	ISO Name ISO Definition XML Tag Type	Clearing System Member Identification Information used to identify a member within a clearing system. ClrSysMmbId ClearingSystemMemberIdentification2
0..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Clearing System Member Identification +++Clearing System Identification	ISO Name ISO Definition XML Tag Type	Clearing System Identification Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed. ClrSysId ClearingSystemIdentification2Choice
XOR 1..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Clearing System Member Identification +++Clearing System Identification ++++Code	ISO Name ISO Definition XML Tag Type	Code Identification of a clearing system, in a coded form as published in an external list. Cd ExternalClearingSystemIdentification1Code

Author (also fact-checker)

XOR 1..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Clearing System Member Identification +++Clearing System Identification ++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Identification code for a clearing system, that has not yet been identified in the list of clearing systems. Prtry Max35Text
1..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Clearing System Member Identification +++Member Identification	ISO Name ISO Definition XML Tag Type	Member Identification Identification of a member of a clearing system. Mmbld Max35Text
0..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Name	ISO Name ISO Definition XML Tag Type	Name Name by which an agent is known and which is usually used to identify that agent. Nm Max140Text
0..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Postal Address	ISO Name ISO Definition XML Tag Type More Details	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress6 See Postal Address .
0..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an agent, as assigned by an institution, using an identification scheme. Othr GenericFinancialIdentification1
1..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Other +++Identification	ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification of a person. Id Max35Text
0..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Other +++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm FinancialIdentificationSchemeName1Choice
XOR 1..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Other +++Scheme Name ++++Code	ISO Name ISO Definition XML Tag Type	Code Name of the identification scheme, in a coded form as published in an external list. Cd ExternalFinancialInstitutionIdentification1Code
XOR 1..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Other +++Scheme Name ++++Proprietary	ISO Name ISO Definition XML Tag Type	Proprietary Name of the identification scheme, in a free text form. Prtry Max35Text

Author (also fact-checker)

0..1	BranchAndFinancialInstitutionIdentification4 +Financial Institution Identification ++Other +++Issuer	ISO Name ISO Definition XML Tag Type	Issuer Entity that assigns the identification. Issr Max35Text
0..1	BranchAndFinancialInstitutionIdentification4 +Branch Identification	ISO Name ISO Definition XML Tag Type LF Usage	Branch Identification Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData2 Not used by Länsförsäkringar Bank
0..1	BranchAndFinancialInstitutionIdentification4 +Branch Identification ++Identification	ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification of a branch of a financial institution. Id Max35Text
0..1	BranchAndFinancialInstitutionIdentification4 +Branch Identification ++Name	ISO Name ISO Definition XML Tag Type	Name Name by which an agent is known and which is usually used to identify that agent. Nm Max140Text
0..1	BranchAndFinancialInstitutionIdentification4 +Branch Identification ++Postal Address	ISO Name ISO Definition XML Tag Type More Details	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress6 See Postal Address .

Author (also fact-checker)

Appendix:

BTC codes

Domain	Family	Sub Family	Domain Code	Family Code	Sub Family Code	Description
Account Management	Misc credit Operations	Charges	ACMT	MCOP	CHRG	Charges - credit
Account Management	Misc credit Operations	Interests	ACMT	MCOP	INTR	Interest - credit
Account Management	Misc credit Operations	Other	ACMT	MCOP	OTHR	Account management - Other
Account Management	Misc Debit Operations	Charges	ACMT	MDOP	CHRG	Charges - debit
Account Management	Misc Debit Operations	Interests	ACMT	MDOP	INTR	Interest - debit
Account Management	Misc Debit Operations	Other	ACMT	MDOP	OTHR	Account management other - debit
Account Management	Opening & Closing	Account Closing	ACMT	OPCL	ACCC	Account closure
Cash Management	Account Balancing	Topping	CAMT	ACCB	TOPG	Account balancing
Loans, Deposits & Syndications	Fixed Term Deposits	Deposit	LDAS	FTDP	DPST	Fixed deposit
Loans, Deposits & Syndications	Fixed Term Deposits	Repayment	LDAS	FTDP	RPMT	Fixed deposit repayment
Loans, Deposits & Syndications	Misc credit Operations	Other	LDAS	MCOP	OTHR	Loan disbursement - credit
Loans, Deposits & Syndications	Misc Debit Operations	Other	LDAS	MDOP	OTHR	Loan repayment - debit
Payments	Customer Card Transactions	Cash deposits	PMNT	CCRD	CDPT	Card - cash deposit - credit

Author (also fact-checker)

Domain	Family	Sub Family	Domain Code	Family Code	Sub Family Code	Description
Payments	Customer Card Transactions	Charges	PMNT	CCRD	CHRG	Card - charges
Payments	Customer Card Transactions	Cash Withdrawal	PMNT	CCRD	CWDL	Card - domestic cash withdrawal - debit
Payments	Customer Card Transactions	Credit card payment	PMNT	CCRD	POSC	Credit card payment
Payments	Customer Card Transactions	Point-of-Sale (POS) Payment - Debit Card	PMNT	CCRD	POSD	Debit card payment
Payments	Customer Card Transactions	Cross border cash withdrawal	PMNT	CCRD	XBCW	Card - cross border cash withdrawal - debit
Payments	Issued Credit Transfer	Charges	PMNT	ICDT	CHRG	Charges - debit
Payments	Issued Credit Transfer	Domestic Credit Transfer	PMNT	ICDT	DMCT	Domestic payment - debit
Payments	Issued Credit Transfer	SEPA Credit Transfer	PMNT	ICDT	ESCT	SEPA payment - debit
Payments	Issued Credit Transfer	Reversal due to payment return	PMNT	ICDT	RRTN	Reversals - debit
Payments	Issued Credit Transfer	Payroll/Salary Payment	PMNT	ICDT	SALA	Salary payment - debit
Payments	Issued Credit Transfer	Cross-Border Credit Transfer	PMNT	ICDT	XBCT	Cross border payment - debit
Payments	Issued Direct Debits	Direct Debet Payment	PMNT	IDDT	PMDD	Autogiro

Author (also fact-checker)

Domain	Family	Sub Family	Domain Code	Family Code	Sub Family Code	Description
Payments	Issued Direct Debits	Reversal Due To Payment Reversal	PMNT	IDDT	PRDD	Autogiro credit reversal - debit
Payments	Issued Real time credit transfers	Charges	PMNT	IRCT	CHRG	Swish - charges
Payments	Issued Real time credit transfers	Domestic Credit transfer	PMNT	IRCT	DMCT	Swish - debit
Payments	Issued Real time credit transfers	Reversal Due To Payment Return	PMNT	IRCT	RRTN	Swish refund- credit
Payments	Misc credit Operations	Others	PMNT	MCOP	OTHR	Other credit payment
Payments	Misc Debit Operations	Others	PMNT	MDOP	OTHR	Other debit payment
Payments	Not Available	Not Available	PMNT	NTAV	NTAV	Other
Payments	Received Credit Transfers	Charges	PMNT	RCDT	CHRG	Charges - debit
Payments	Received Credit Transfers	Domestic Credit Transfer	PMNT	RCDT	DMCT	Domestic payment - credit
Payments	Received Credit Transfers	Reversal Due To Payment Return	PMNT	RCDT	RRTN	Reversals - credit
Payments	Received Credit Transfers	Payroll/Salary Payment	PMNT	RCDT	SALA	Salary payment - credit
Payments	Received Credit Transfers	Cross-Border Credit Transfer	PMNT	RCDT	XBCT	Cross border payment - credit
Payments	Received Cheques	Cash Letter	PMNT	RCHQ	CASH	Cashier check
Payments	Received Cheques	Cheque	PMNT	RCHQ	CCHQ	Cheque

Author (also fact-checker)

Domain	Family	Sub Family	Domain Code	Family Code	Sub Family Code	Description
Payments	Received Direct Debits	Direct Debet	PMNT	RDDT	PMDD	Autogiro
Payments	Received Direct Debits	Reversal Due To Payment Reversal	PMNT	RDDT	PRDD	Autogiro debit reversal - credit
Payments	Received Real time credit transfers	Charges	PMNT	RRCT	CHRG	Swish - charges
Payments	Received Real time credit transfers	Domestic Credit transfer	PMNT	RRCT	DMCT	Swish - credit
Payments	Received Real time credit transfers	Reversal Due To Payment Return	PMNT	RRCT	RRTN	Swish refund - debit

Author (also fact-checker)

Changelog

Version 1.2

Section	Change
2.6.5	Added chapter regarding local instrument code
2.6.7	Added clarification regarding different ID fields in remittance information
2.6.7.2	Added chapter about Extended remittance information (ERI)
3.1.3	Changed multiplicity for unstructured remittance info